



PRODUCT NUMBER: 3301165
Max LS-500 Refill

[Learn more about our products at howardleight.com](http://howardleight.com)

>



Overview

Reference Number

3301165

Product Type

Hearing Protection

Range

Earplugs

Line

Disposable Earplugs

Brand

Howard Leight by Honeywell

Industry

- Industry
- Administration
- Agriculture
- Army - Defence
- ATEX environment
- Automotive and Part Manufacturer
- Aviation
- Building and Construction
- Catering
- Chemical Industries
- Energy or Electricity
- Fire Protection brigades
- Fishing
- Food Industries
- Foundry
- Glass Industries
- Green Spaces
- Homeland defense
- Industrial Cleaning
- Iron and steel industry
- Laboratory
- Logistics
- Maintenance
- Medical and Pharmaceutical
- Metal steel
- Mining and Quarrying
- Offshore
- Paper Industries
- Petro-chemical
- Printing Industries
- Services
- Ship Building
- Telecoms
- Textile Industries
- Transportation
- Utilities
- Water treatment
- Welding
- Wood Industries

Product Use

MAX LS-500 Dispenser Refill, Disposable

Features & Benefits

Feature

POLYURETHANE FOAM Soft foam delivers superior long-wearing comfort and solid performance. BELL-SHAPED DESIGN Delivers maximum in-ear comfort without backing out of the ear canal, easier to insert. SMOOTH, SOIL-RESISTANT SKIN Prevents dirt or other substances from accumulating on skin or entering ear canal.

Benefit

Workers who need to block out loud noise demand the best protection and comfort available in an earplug. That's where

Max comes in. The world's most-used polyurethane earplug, Max offers superior noise-blocking performance in a single-use earplug. Max's new enhanced contoured shape is easier to insert and resists backing out of the ear canal, while its softer foam delivers superior long-wearing comfort - delivering solid performance that your workers can depend on.

Technical Description

SNR (dB)

37

H (dB)

36

M (dB)

35

L (dB)

34

Attenuation Data

Frequency (Hz) Frequenz (Hz) Fréquence (Hz)	63	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB) Mittlere Dämmung (dB) Atténuation moyenne (dB)	34.6	37.1	37.4	38.8	38.2	37.9	47.3	44.8
Standard Deviation (dB) Standardabweichung (dB) Déviation standard (dB)	3.0	4.5	4.3	3.7	3.5	4.0	3.5	7.2
Assumed Protection (dB) Angenommener (dB) Protection supposée (dB)	31.6	32.6	33.1	35.1	34.7	33.9	43.8	37.6

Size

Fits All

Color

Orange

Shape

bell

Corded

No

Weight (grs)

0.59

Certifications

EU Category PPE

3

Quality Assurance

ISO 9001 / 2000

EU Certification

2777/12542-01/E00-00

Literature & Documents

PIC SKU - Pictures

<http://www.honeywellsafety.com/assets/0/324/500/51887/31b9f20ec0f148b89015157cb7f5e40f.jpg>

Additional Information

User Manual

Instruction Manual - Max (global)

Maintenance

Life Cycle

These plugs must be disposed of and replaced after each wearing.

Storage Information

All earplugs should be stored before and between usages in a way that protects them from dirt, grease, and other contaminants.

Care Instructions

Disposable earplugs are made of either TPE (Thermoplastic elastomers) or polyurethane foam. Washing and cleaning of disposable earplugs are not recommended. These plugs must be disposed of and replaced after each wearing. Excessive moisture reduces the attenuation and slows down the foam recovery which may lead to improper fit.

Packaging

EAN Code

033552003717