

DATASHEET

HMS DOUBLE TRI CB 2.0



GENERAL

| | | | |
|------------------------|---------------|---------------|---|
| Art.Nr: | H-204 | Standards: | EN 12275-H:2013, EN 362-B:2004, UIAA 121:2018 |
| GTIN: | 4030281303794 | Net weight: | 0.10 kg |
| E-class number: | 40-02-01-05 | Gross weight: | 0.10 kg |
| Customs tariff number: | 76169990 | | |

DATASHEET

HMS DOUBLE TRI CB 2.0

HMS carabiner with DOUBLE TWIST Gate. The DOUBLE gate with patented 180° technology allows the locking sleeve to be turned in two directions. This makes the carabiner equally easy to use for left- and right-handed users.

- HMS carabiner with wide apex offers plenty of space for equipment (e.g. ropes, slings, etc.)
- Patented double gate can be used by both left- and right-handed users
- I-profile body optimizes the strength-to-weight ratio
- Enlarged cross-section in areas exposed to abrasion (apex and base)
- Compact key-lock nose and large opening width for quick and easy attachment and removal of anchor points

FEATURES

| | |
|-----------------------------|--|
| Swivel: | No |
| Carabiner properties: | Corrosion resistance |
| Application areas: | Arborists, RBA rigging |
| Fallindicator: | No |
| Colour: | Orange, Grey |
| Breaking load - lengthways: | 25.00 kN |
| Breaking load - open: | 7.00 kN |
| Breaking load - crosswise: | 7.00 kN |
| Form fit: | Key Lock |
| Carabiner type: | Type H (EN 12275:2013), Type B (EN 362:2004) |
| Maximum lifetime: | 30 years |
| Maximum temperature: | 45 °C |
| Minimum temperature: | -35 °C |
| Standard ANSI: | No |
| Standard CSA: | No |
| Standard UIAA: | Yes |
| Anti-twist device: | Yes |
| Carabiner clasp: | Double-Triple |

DIMENSIONS

| | |
|---------------------|-----------|
| Opening width: | 24 mm |
| Working load limit: | 250.00 kg |

MATERIAL

DATASHEET

HMS DOUBLE TRI CB 2.0

Material:

Aluminium
