

DATASHEET

CONCEPT SGL



GENERAL

Art.Nr:	H-281-SGL
GTIN:	8056734836929
E-class number:	40-02-01-05
Customs tariff number:	76169990990001

Standards:	EN 12275-H:2013, EN 362-A/T:2004, UIAA 121
Net weight:	0.08 kg
Gross weight:	0.08 kg

DATASHEET

CONCEPT SGL

Hot forged light alloy HMS carabiner with screwgate, conceived for connecting various devices and for use with the Munter hitch.

Main features:

- emphasized double T beam construction, for an optimal weight / strength ratio;
- light and shaped, for a better grip;
- catch-free nose avoids snagging when clipping and unclipping;
- with ACL system to prevent cross loading.

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Silver, Light blue, Grey
Breaking load - lengthways:	23.00 kN
Breaking load - open:	7.00 kN
Breaking load - crosswise:	10.00 kN
Form fit:	Key Lock
Carabiner type:	Type H (EN 12275:2013), Type A (EN 362:2004), Type T (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

DATASHEET

CONCEPT SGL

Standard ANSI:	No
Standard CSA:	No
Standard UIAA:	Yes
Anti-twist device:	Yes
Carabiner clasp:	Screw

DIMENSIONS

Opening width:	21 mm
----------------	-------

MATERIAL

Material:	Aluminium
-----------	-----------