

# DATASHEET

## CONCEPT TGL



### GENERAL

Art.Nr:	H-281-TGL	Standards:	EN 12275-H:2013, EN 362-A/T:2004, UIAA 121
GTIN:	8056734836912	Net weight:	0.08 kg
E-class number:	40-02-01-05	Gross weight:	0.08 kg
Customs tariff number:	76169990990001		

# DATASHEET

## CONCEPT TGL

Hot forged light alloy HMS carabiner with triplex twist-lock gate, conceived for connecting various devices and for use with the Munter hitch.

### Main features:

- emphasized double T beam construction, for an optimal weight / strength ratio;
- light and shaped, for a better grip;
- catch-free nose avoids snagging when clipping and unclipping;
- with ACL system to prevent cross loading.

### FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Grey, Silver, Light blue
Breaking load - lengthways:	23.00 kN
Breaking load - open:	7.00 kN
Breaking load - crosswise:	8.00 kN
Form fit:	Key Lock
Carabiner type:	Type H (EN 12275:2013), Type A (EN 362:2004), Type T (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

# DATASHEET

## CONCEPT TGL

Standard ANSI:	No
Standard UIAA:	Yes
Anti-twist device:	Yes
Carabiner clasp:	Triple

### **DIMENSIONS**

Opening width:	21 mm
----------------	-------

### **MATERIAL**

Material:	Aluminium
-----------	-----------