

DATASHEET

CONCEPT SGL HC



GENERAL

Art.Nr:	H-282-SGL	Standards:	EN 12275-H:2013,EN 362-A/T:2004,UIAA 121
GTIN:	8056734832426	Net weight:	0.08 kg
E-class number:	40-02-01-05	Gross weight:	0.08 kg
Customs tariff number:	76169990990001		

DATASHEET

CONCEPT SGL HC

Hot forged light alloy HMS carabiner with screwgate, conceived for connecting various devices and for use with the Munter hitch.

Main features:

- emphasized double T beam construction, for an optimal weight / strength ratio;
- light and shaped, for a better grip;
- catch-free nose avoids snagging when clipping and unclipping;
- with ACL system to prevent cross loading;
 - with special wear-proof hard coat anodizing, ideal for intensive and prolonged use.

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Brown, Silver, Orange
Breaking load - lengthways:	23.00 kN
Breaking load - open:	7.00 kN
Breaking load - crosswise:	10.00 kN
Form fit:	Key Lock
Carabiner type:	Type H (EN 12275:2013), Type A (EN 362:2004), Type T (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	No

DATASHEET

CONCEPT SGL HC

Standard CSA:	No
Standard UIAA:	Yes
Anti-twist device:	Yes
Carabiner clasp:	Screw

DIMENSIONS

Opening width:	21 mm
----------------	-------

MATERIAL

Material:	Aluminium
-----------	-----------