

# DATASHEET

## PILLAR TG



### GENERAL

Art.Nr:	H-285-TG	Standards:	EN 12275-B:2013, EN 362-B:2004, UIAA 121
GTIN:	8057733305638	Net weight:	0.08 kg
E-class number:	40-02-01-05	Gross weight:	0.08 kg
Customs tariff number:	76169990990001		

# DATASHEET

## PILLAR TG

Light alloy oval-shaped carabiner with triplex twist-lock gate.

Main features:

- designed for the positioning of large-section devices (e.g.pulleys, ascenders, retractable fall arresters, etc.);
- particularly suited for use on belay stations, hauling and rescue maneuvers;
- catch-free nose avoids snagging when clipping and unclipping.

### FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Black
Breaking load - lengthways:	24.00 kN
Breaking load - open:	7.00 kN
Breaking load - crosswise:	8.00 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 12275: 2013), Type B (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	No

## DATASHEET

## PILLAR TG

Standard CSA:	No
Standard UIAA:	Yes
Anti-twist device:	No
Carabiner clasp:	Triple

**DIMENSIONS**

Opening width:	21 mm
----------------	-------

**MATERIAL**

Material:	Aluminium
-----------	-----------