

DATASHEET

SNAPPY SG



GENERAL

Art.Nr:	H-289-SG	Standards:	EN 12275-H:2013, EN 362-B:2004, UIAA 121
GTIN:	8056734830842	Net weight:	0.09 kg
E-class number:	40-02-01-05	Gross weight:	0.09 kg
Customs tariff number:	76169990990001		

DATASHEET

SNAPPY SG

Hot forged light alloy HMS carabiner with screwgate, conceived for connecting various devices and for use with the Munter hitch.

Main features:

- large aperture and wide radius to facilitate rope sliding;
- wide inner space allows for multipurpose use on the belay station and use of a Munter hitch;
- catch-free nose to avoid snagging clipping and unclipping.

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Silver
Breaking load - lengthways:	23.00 kN
Breaking load - open:	9.00 kN
Breaking load - crosswise:	10.00 kN
Form fit:	Key Lock
Carabiner type:	Type H (EN 12275: 2013), Type B (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	No

DATASHEET

SNAPPY SG

Standard CSA:	No
Standard UIAA:	Yes
Anti-twist device:	No
Carabiner clasp:	Screw

DIMENSIONS

Opening width:	22 mm
----------------	-------

MATERIAL

Material:	Aluminium
-----------	-----------