

DATASHEET

OVX TG



GENERAL

Art.Nr:	H-298-TG	Standards:	EN 12275-B:2013, EN 362-B:2004, UIAA 121
GTIN:	8056734832426	Net weight:	0.06 kg
E-class number:	40-02-01-05	Gross weight:	0.06 kg
Customs tariff number:	76169990990001		

DATASHEET

OVX TG

Hot-forged light-alloy oval carabiner with reduced dimensions and triplex gate. Ideal for rope access work, work at height and rescue operations, in particular where space for manoeuvring is limited.

Main features:

- only 95 mm long, to leave more room for manoeuvres;
- curved shape of the spine, for improved handling and to maximize gate opening;
- oval shape, for optimal placement of equipment and ropes;
- increased cross-section at contact points, for enhanced rope glide and wear resistance;
- the profile between the nose and the interior of the connector is shaped with no discontinuities, which makes it easier to clip and unclip to anchors, tools and ropes;
- catch-free closure.

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Arborists, RBA rigging, Various
Fallindicator:	No
Colour:	Orange, Silver, Anthracite
Breaking load - lengthways:	24.00 kN
Breaking load - open:	7.00 kN
Breaking load - crosswise:	9.00 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 12275: 2013), Type B (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	No
Standard CSA:	No
Standard UIAA:	Yes
Anti-twist device:	No
Carabiner clasp:	Triple

DIMENSIONS

Opening width:	17 mm
----------------	-------

MATERIAL

Material:	Aluminium
-----------	-----------

DATASHEET

OVX TG

