

# DATASHEET

## AXIS HMS TG



### GENERAL

Art.Nr:	H-310-TG
GTIN:	8056734836943
E-class number:	40-02-01-05
Customs tariff number:	76169990990001

Standards:	EN 12275-H:2013, EN 362-A/T:2004, UIAA 121
Net weight:	0.09 kg
Gross weight:	0.09 kg

# DATASHEET

## AXIS HMS TG

Large HMS carabiner with wide opening and triplex twist-lock gate, made of hot-forged light alloy, designed for use in mountaineering, recovery manoeuvres and rescue operations.

### Main features:

- shape guarantees correct axial loading relative to rope and other devices;
- large size and ample width to allow use of Munter hitch knot, the securing of more than one rope, slings or devices and rope manoeuvres in general;
- accentuated double-T profile, for an excellent weight/load ratio;
- lightened and shaped form for improved ease of holding;
- catch-free closure to avoid accidental tangling during use.

### FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Grey, Silver, Green
Breaking load - lengthways:	25.00 kN
Breaking load - open:	7.00 kN
Breaking load - crosswise:	8.00 kN
Form fit:	Key Lock
Carabiner type:	Type H (EN 12275:2013), Type B (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	No

# DATASHEET

## AXIS HMS TG

Standard CSA:	No
Standard UIAA:	Yes
Anti-twist device:	No
Carabiner clasp:	Triple

### **DIMENSIONS**

Opening width:	23 mm
----------------	-------

### **MATERIAL**

Material:	Aluminium
-----------	-----------