

DATASHEET

Q-LINK 10



GENERAL

Art.Nr:	H-320-10	Standards:	EN 12275-Q:2013, EN 362-Q:2004, UIAA 121
E-class number:	40-02-01-05	Net weight:	0.14 kg
Customs tariff number:	73269098900003	Gross weight:	0.14 kg

DATASHEET

Q-LINK 10

Galvanized-steel quick link, oval shaped Ø 10 mm, extremely sturdy and designed to withstand high loads on all axes. Ideal to be used as a lowering anchorage, for fixed quickdraws, work at height, industrial safety and rescue.

When closed with a wrench, it becomes a semi-permanent anchor.

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Silver
Breaking load - lengthways:	55.00 kN
Breaking load - crosswise:	10.00 kN
Form fit:	Hook-Nose
Carabiner type:	Type Q (EN 12275:2013), Type Q (EN 362:2004)
Maximum lifetime:	30 years
Standard ANSI:	No
Standard CSA:	No
Standard UIAA:	Yes
Anti-twist device:	No

DATASHEET

Q-LINK 10

Carabiner clasp: Screw

DIMENSIONS

Opening width: 12 mm

MATERIAL

Material: Steel
