

# DATASHEET

## Q-LINK HM



### GENERAL

Art.Nr:	H-325-10
E-class number:	40-02-01-05
Customs tariff number:	73269098900003

Net weight:	0.06 kg
Gross weight:	0.06 kg

# DATASHEET

## Q-LINK HM

Galvanized-steel quick link half moon shaped Ø 10 mm, extremely sturdy and designed to withstand high loads on all axes. Ideal to secure the two attachment points of a speleology harness.

When closed with a wrench, it becomes a semi-permanent anchor.

### FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various, Arborists, Elevator construction, Emergency, Facades cleaning, Flat roof construction, High Rack storage, High ropes courses, LEAF, Mobile platforms, Mobile Work Platforms, Off Shore Industry, RBA rigging, Rescue, Roofers, Route construction, Scaffolding, Shaft, Steelwork, Telco energy, Wind energy, Working in confined spaces
Fallindicator:	No
Colour:	Silver
Breaking load - lengthways:	45.00 kN
Breaking load - open:	0.00 kN
Breaking load - crosswise:	10.00 kN
Form fit:	Hook-Nose
Carabiner type:	Type Q (EN 12275: 2013), Type Q (EN 362:2004)
Maximum lifetime:	30 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C
Standard ANSI:	No

# DATASHEET

## Q-LINK HM

Standard UIAA:	Yes
----------------	-----

Anti-twist device:	No
--------------------	----

Carabiner clasp:	Screw
------------------	-------

### **DIMENSIONS**

Opening width:	10 mm
----------------	-------

### **MATERIAL**

Material:	Steel
-----------	-------